

Ultra Prime 30

Pilot Freeze Dryer



Transform Your Workflow.

The Ultra Prime 30 is a state-of-the-art freeze-dryer engineered for superior performance, repeatability, and sustainability. Designed with advanced LyoLogic HMI technology and a refined, space-saving footprint, Ultra Prime 30 delivers smoother operation, improved efficiency, and reduced environmental impact, setting a new standard for laboratory and small-scale production freeze-drying.

Key Features & Benefits

- **Direct Vapor Port Design**
Engineered to mitigate choked flow, the direct vapor port delivers **smoother vapor transfer** and more efficient freeze-drying.
- **Space Saving Footprint**
With multiple standard layout options, the Ultra Prime 30 minimizes overall footprint without compromising performance, an ideal solution for space-conscious laboratory environments.
- **Advanced LyoLogic HMI Interface**
Integrated LyoLogic HMI provides an intuitive user experience, enabling precise control, simplified operation, and improved repeatability.
- **Enhanced Cycle Efficiency**
Upgraded system performance supports improved **cycle efficiency**, helping reduce energy consumption, operating costs, and environmental impact.
- **Efficient Cleaning & Maintenance**
Smooth-walled condenser and easy defrost system **minimize turnaround time** and **simplify cleaning**.
- **Customizable Configurations**
Options include bulk or stoppering layouts, up to 15 shelves, solvent packages, and configurations for **cleanroom installations**.
- **Lower GWP Refrigerants**
Optimized cooling performance with modern **CFC-free** refrigerants
- **Modifiable**
Easily latch one or multiple shelves in seconds to allow for maximum flexibility when changing container sizes



Why Choose Ultra Prime 30?

- Handles a wide variety of applications with precise temperature control (shelf temperatures down to -70°C, condenser down to -85°C)
- Flexible system configurations for both high-moisture and low-moisture products
- Intuitive interface reduces operator training time
- Compact footprint maximizes lab space while maintaining high throughput
- Smooth wall condenser enables rapid turn around time
- Comprehensive Training Options
- Complete Service Solutions



Specifications

Lowest shelf temperature (50 Hz / 60 Hz)	≤ -67°C / -70°C
Shelf temperature control range*	-55 to 65°C
Shelf Temperature Control Range Tolerance	+/- 0.5 °C
Vacuum Level Control Range	0.067 – 0.67 mbar (50 – 500 mTorr)
Volume-based leak rate§	≤ 0.0036 mbar•L/s (≤ 0.0027 Torr•L/s)
Lowest system vacuum§	≤ 0.2 mbar (≤ 15 mTorr)

Electrical Requirements

Voltage	Phase	Frequency	Breaker Amperage	Peak Current	Peak Power
208 VAC	1 Φ	60 Hz	40 A	25 A	5,200 VA
230 VAC	1 Φ	50 Hz	40 A	25 A	5,750 VA
400 VAC	3 Φ	50 Hz	32 A	15 A	6,000 VA

Shelf Configuration

Number of Shelves	Shelf Clearance with One Shelf Latched	Recommended Vials†
8 Shelves	99.2 mm (3.90 in)	30R or smaller
9 Shelves	86.9 mm (3.42 in)	25R or smaller
10 Shelves	76.8 mm (3.02 in)	20R or smaller
11 Shelves	68.7 mm (2.70 in)	10R or smaller
12 Shelves	61.9 mm (2.43 in)	8R or smaller
13 Shelves	56.2 mm (2.21 in)	6R or smaller
14 Shelves	51.3 mm (2.01 in)	2R or smaller
15 Shelves	47 mm (1.85 in)	2R or smaller

Additional Information

Construction	316L stainless steel shelves, product chamber and condenser chamber
Defrost type	Hot gas
Vapor Port	15.2 cm (6 in) Wide 20.3 cm (8 in) Narrow / Cleanroom
Temperature uniformity	± 1.0°C
Noise Level	75 dBA

Performance specifications are based on SP test data from units operating at an ambient room temperature of approximately 20°C. SP recommends an optimum operating range of 15-25°C (59-77°F). For full specifications please contact your regional product specialist.

* Shelf fluid inlet temperature controlled to within ± 0.5°C of the setpoint within the Shelf Temperature Control Range when at 100 mTorr.

§ Vacuum specifications are based on Scientific Products test data from similar units equipped with a two-stage rotary vane vacuum pump and EPDM seals.

† Recommended Maximum Vial Size without latching shelves using standard shelf clearances

Refrigerant Information

	Gas 1	Gas 2
F Gas	R1270	R170
GWP	2	5.5
EPA SNAP	IPR	VLTR
Safety Class	A3	A3
Total CO ₂ E	0.00168 (AC); TBC (WC)	

Utility Requirements

	Air-Cooled	Water-Cooled
Compressed air (for units with isolation valve)	80 psig (5.5 bar)	
Inert Gas for Backfilling	3-5 PSIG (0.2-0.35 bar g)	
Ambient Room Temperature	15 -25°C (59 -77°F)	
Cooling Water	N/A	4-12 Lpm (1-3 gpm) 5-25°C, 2-4 bar (30-60 psi)
Heat Output Room, Peak	11,500 BTU/h (3.4 kW)	4,100 BTU/h (1.2 kW)

Vial Capacity (estimated)

Vial Size	Diameter (mm)	Height (mm)	Height Approximately 15mm with Stopper and clearance (mm)	Tray 10x20in
2R	16	35	50	519
6R	22	40	55	264
10R	24	45	60	220
20R	30	55	70	144
30R	30	75	90	144

	Standard Configuration	Narrow Configuration	Cleanroom Configuration
Max. weight	592 Kg (1,305 lb)	838 Kg (1,849 lb)	
Max. weight crated (est.)	721 Kg (1,590 lb)	993 Kg (2,190 lb)	



935 Mearns Road, Warminster, PA 18974 USA | scientificproducts.com
+1-800.523.2327 | hello@scientificproducts.com

©2023 SP Industries, Inc. SP reserves the right to change specifications without notice. All trademarks referenced in this document are registered or common law trademarks of SP Industries, Inc. or its affiliates in the U.S. and/or other countries. *Other specific brand or product names may be registered trademarks of their respective companies.